

SENSORS
GPS SENSORS



LIDAR-Lite v3

PART NUMBER: 010-01722-00

\$149.99 USD

ADD TO CART

Processing time is 1–3 business days.



OVERVIEW

SPECS

- Unit size (HxWxD): 40 x 48 x 20 mm (1.6" x 1.9" x 0.8")
- Weight: 22 g (0.77 oz)
- Resolution: 1 cm
- Accuracy: +/- 2.5 cm at distances greater than 1 meter. Refer to operating manual for complete operating specifications.
- Range: 5 cm to 40 meters
- Update rate: up to 500 Hz
- Interface: I2C or PWM

- Power (operating voltage): 4.75-5 VDC; 6 V Max
- Current consumption: 105ma, idle; 130ma, continuous
- Operating temperature: -20 to 60° C
- Laser wave length/Peak power: 905 nm/1.3 watts
- Beam divergence: 8 m Radian
- Optical aperture: 12.5 mm
- Regulatory approvals: CLASS 1 LASER PRODUCT CLASSIFIED EN/EIC 60825-1 2014. This product is in conformity with performance standards for laser products under 21 CFR 1040, except with respect to those characteristics authorized by Variance Number FDA-2016-V-2943 effective September 27, 2016. System contains no user serviceable components. Repair or service of the system is only to be handled by factory trained technicians. No service by the user is allowed.

IN THE BOX

RESELLERS

ACCESSORIES

Related

[Manuals](#)

[Software](#)

[Support Center](#)

Want more features?



GPS 18x 5Hz™

\$199.99 USD

[Preferințele cookie](#)

